

DEPENDENT RESURVEY, SUBDIVISIONAL LINES, T. 16 N., R. 63 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16N	R63E
S 6	S 5
S 7	S 8

1967

bury the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Point for the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., at proportionate distance, bears N. $0^{\circ} 13' E.$, 81.54 chs. dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N	R63E
S 32	S 33
S 5	S 4
T16N	R63E

1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this cor., the cor. of secs. 5, 6, 31 and 32, Tps. 16 and 17 N., R. 63 E., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears S. $87^{\circ} 08' W.$, 76.19 chs. dist.

From the same cor., the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, Tps. 16 and 17 N., R. 63 E., monumented with a squared wooden post, 2 ins. square, 18 ins. long, loosely set alongside a sandstone, 8x8x24 ins., with a steel pin set in the center and firmly set in the ground, bears N. $87^{\circ} 08' E.$, 114.285 chs. dist. This position has long been recognized as the cor. by local residents and is accepted as the best evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N	R63E
$\frac{1}{4}$	S 34
	S 3
T16N	R63E

1967