

INDEPENDENT RESURVEY OF A PORTION OF THE THIRD STANDARD
PARALLEL NORTH, THROUGH RANGE 27 EAST

| CHAINS | |
|--------|---|
| | WEST, along the S. bdy. of sec. 32. |
| | Over mountainous terrain, through medium dense undergrowth; asc. 50 ft. over a SE. slope. |
| 6.00 | Ridge, bears NE. and SW.; desc. 40 ft. over a rolling NNW. slope. |
| 26.00 | Low saddle, drains NNE. and SSW.; asc. 50 ft. over a gentle E. slope. |
| 40.00 | Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to rock and in a mound of stone, $3\frac{1}{2}$ ft. base to cap, with brass cap mkd. |
| | <p style="text-align: center;">SC T16N R27E <u>$\frac{1}{4}$ S 32</u></p> |
| | 1967 |
| | Over gently rolling land draining N. |
| 76.70 | Low rocky spur, slopes N.; desc. 20 ft. over a WNW. slope. |
| 80.00 | Point for the standard cor. of secs. 31 and 32, situated in a shallow swale draining N. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">SC T16N R27E <u>S 31 S 32</u></p> |
| | 1967 |
| | raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. |
| | <p>Land, mountainous to rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush and grasses.</p> |
| | WEST, along the S. bdy. of sec. 31. |
| | Over mountainous terrain, through medium dense undergrowth; asc. 160 ft. over an E. slope changing to S. |
| 22.50 | Spur, slopes SW.; desc. 110 ft. over a WNW. slope gradually changing to a gentle S. slope. |
| 40.00 | Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to cap, with brass cap mkd. |
| | <p style="text-align: center;">SC T16N R27E <u>$\frac{1}{4}$ S 31</u></p> |
| | 1967 |