

INDEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 17 N., R. 27 E.

CHAINS									
45.00	Saddle, drains E. and W.; desc. 10 ft. along a gentle S. slope.								
62.63	The closing cor. of secs. 5 and 6, hereinafter described. Desc. 20 ft. over a SW. slope.								
65.00	Swale, drains SSE.; asc. 90 ft. over an E. slope.								
78.20	Rocky spur, bears SE. and NW.; desc. 20 ft. over a SW. slope.								
80.00	Point for the cor. of secs. 31 and 32.								
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to rock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T17N</td> <td>R27E</td> </tr> <tr> <td><u>S 31</u></td> <td><u>S 32</u></td> </tr> <tr> <td colspan="2" style="text-align: center;">S 6</td> </tr> <tr> <td>T16N</td> <td>R27E</td> </tr> </table>	T17N	R27E	<u>S 31</u>	<u>S 32</u>	S 6		T16N	R27E
T17N	R27E								
<u>S 31</u>	<u>S 32</u>								
S 6									
T16N	R27E								
	1967								
	From this corner, the original cor. of secs. 5, 6, 31 and 32, bears N. 26 3/4° W., 2.54 chs. dist., monumented with a basalt stone, 18x10x8 ins., plainly mkd. with 5 grooves on the E. face and 1 groove on the W. face. The corner stone is firmly set in a collar of stone and exposed 12 ins. above the ground. I destroy all evidence of the corner and accessories.								
	Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush, shadscale and grasses.								
	WEST, along the S. bdy. of sec. 31.								
	Over mountainous land, through medium dense undergrowth; desc. 120 ft. over a rolling SSW. slope.								
20.00	Draw, drains S.; asc. E. slope.								
22.63	The N. ¼ sec. cor. of sec. 6, hereinafter described.								
23.00	Low rocky spur slopes S.; desc. 50 ft. over a W. slope.								
30.00	Swale, drains S.; asc. 100 ft. over a rolling SE. slope.								
38.80	Spur, slopes SW. from N. A prominent sharp rock outcrop bears S. 0.50 chs. dist.; desc. 30 ft. over a W. slope.								
40.00	Point for the S. ¼ sec. cor. of sec. 31.								
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to rock and in a mound of stone, 3½ ft. base to cap, with brass cap mkd.								