

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 27 E.

CHAINS
80.00

Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N	R27E
S 11	S 12
S 14	S 13

1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling to mountainous.

Soil, clay sand and rocky.

Undergrowth, greasewood, sagebrush and grasses.

N. 89° 56' E., bet. secs. 12 and 13.

Over mountainous land, through scattered undergrowth; desc. 150 ft. over a sandy E. slope.

9.00 Ravine, drains SE.; asc. 70 ft. along a rocky S. slope.

17.00 Top of ascent on S. slope.; desc. 70 ft. along S. slope.

27.00 Slope changes to E.; desc. 150 ft. over an E. slope.

34.00 Base of steep descent, bears N. and S.; desc. over a gentle E. slope.

40.00 Point for the ¼ sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N	R27E
¼	S 12
	S 13

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 50 ft. over a gentle E. slope to the closing cor.

49.80 Trail road, bears NNE. and SSW.

57.40 Trail road, bears N. and S.

62.80 Intersect the W. bdy. of T. 16 N., R. 28 E.

Point for the closing cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N		
R27E	R28E	
CC	S 12	S 18
	S 13	

1967