

## SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 27 E.

CHAINS	
47.00	Asc. 30 ft. over a NE. slope. Low spur, slopes NE.; desc. 30 ft. over a NW. slope.
49.40	Shallow ravine, drains NE.; asc. 320 ft. over an ENE. slope gradually changing to a NNE. slope.
80.00	Point for the 80 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to rock and in a mound of stone, 3½ ft. base to cap, with brass cap mkd.
	T16N R27E 1/16 — S 19 — 80 S 30
	1967
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Asc. over a NNE. slope.
81.00	Ridge, bears SSE. and NW.; desc. 10 ft. over a W. slope.
82.50	Fence, bears SE. and NW.; desc. 160 ft. over a W. slope.
94.50	Ravine, drains NNW.; asc. 40 ft. over a NNE. slope.
99.00	Low spur, slopes N.; desc. 10 ft. over a WNW. slope.
99.73	Intersect the E. bdy. of T. 16 N., R. 26 E. Point for closing cor. of secs. 19 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T16N R26E R27E S 25   S 19 S 30 CC
	1967
	from this corner  The cor. of secs. 24 and 25, T. 16 N., R. 26 E., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears NORTH, 7.57 chs. dist. I add the mks. S 19 to the right half of the brass cap, and the date 1967.  The ¼ sec. cor. of sec. 25, T. 16 N., R. 26 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears SOUTH, 32.43 chs. dist.  Land, rolling to mountainous. Soil, sandy clay and rocky. Undergrowth, sagebrush, shadscale and grasses.