

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 27 E.

CHAINS

40.00

Point for the 1/4 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N R27E  
 1/4 S 18  
 S 19

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Asc. 30 ft. over a SE. slope.

48.00

Low saddle, drains E. and NW.; desc. 50 ft. over a NW. slope.

56.20

Shallow draw, drains NNW.; asc. 100 ft. over an E. slope.

67.00

Top of ascent; over gently rolling land.

80.00

Point for the 80 1/16 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to rock and in a collar of stone, with brass cap mkd.

T16N R27E  
 1/16 S 18 80  
 S 19

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Asc. 50 ft. over an E. slope.

99.58

Intersect the E. bdy. of T. 16 N., R. 26 E.

Point for the closing cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to rock and in a collar of stone, with brass cap mkd.

T16N  
 R26E R27E  
 S 24 | S 18 CC  
 S 19

1967

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

from this corner

The cor. of secs. 13 and 24, T. 16 N., R. 26 E., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears NORTH, 7.57 chs. dist. I add the mks. S 18 to the right half of the brass cap, and the date 1967.