

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 27 E.

CHAINS 57.80	Fence, bears NNE. and SSW.
80.00	The cor. of secs. 7, 8, 17 and 18. Land, rolling to nearly level. Soil, sandy clay. Undergrowth, sagebrush and grasses.
	WEST, bet. secs. 7 and 18. Over mountainous land, through scattered undergrowth; asc. 90 ft. over a N. slope gradually changing to a NE. slope.
12.00	Spur, slopes ESE.; asc. 20 ft. along a rolling S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T16N R27E $\frac{1}{4}$ $\frac{S \ 7}{S \ 18}$ 1967 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Asc. 110 ft. over a SE. slope.
48.80	Summit of a knob on a spur sloping S.; desc. 280 ft. over a WSW. slope gradually changing to a SW. slope.
80.00	Point for the 80 $\frac{1}{16}$ sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T16N R27E 1/16 $\frac{S \ 7}{S \ 18}$ 80 1967 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Desc. 40 ft. over a gentle SW. slope.
99.44	Intersect the E. bdy. of T. 16 N., R. 26 E. Point for the closing cor. of secs. 7 and 18, situated in a trail road bearing ESE. and WNW. Bury an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., with the cap 10 ins. below the road surface and mkd.