

SURVEY OF THE SUBDIVISIONAL LINES, T. 16 N., R. 27 E.

CHAINS

- 7.60 Spur, slopes SW.; desc. 180 ft. over a WSW. slope.
- 19.50 Fence, bears SSE. and NNW.; desc. 30 ft. over a W. slope.
- 21.00 Trail road, bears SSE. and NNW.; desc. 20 ft. over a W. slope.
- 24.00 Swale, drains NNW.; asc. 250 ft. over a sandy NE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to rock and in a mound of stone, $3\frac{1}{2}$ ft. base to cap, with brass cap mkd.

$$\begin{array}{r} \text{T16N R27E} \\ \frac{1}{4} \begin{array}{l} \text{S } 6 \\ \text{S } 7 \end{array} \end{array}$$

1967

Asc. 30 ft. over a NE. slope.

- 44.00 Ridge, bears SE. and NW.; desc. 270 ft. over a rolling SW. slope.

- 59.70 Shallow ravine, drains SSW.; desc. 70 ft. over a gently rolling SW. slope.

- 80.00 Point for the $80 \frac{1}{16}$ sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T16N R27E} \\ 1/16 \begin{array}{l} \text{S } 6 \\ \text{S } 7 \end{array} \text{---}80 \end{array}$$

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 30 ft. over a SW. slope.

- 90.40 Trail road, bears ESE. and WNW.; desc. 20 ft. over a SW. slope.

- 93.10 Wash, 15 lks. wide, 2 ft. deep, drains NW.; over a gentle NNE. slope.

- 99.26 Intersect the E. bdy. of T. 16 N., R. 26 E.

Point for the closing cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T16N} \\ \text{R26E R27E} \\ \text{S } 12 \left| \begin{array}{l} \text{S } 6 \\ \text{S } 7 \end{array} \right. \text{CC} \end{array}$$

1967