CHAINS

29.00

40.26

DEPENDENT RESURVEY OF THE FRACTIONAL WEST BOUNDARY OF T. 16 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by Reilly and Magee, U. S. Deputy Surveyors, in 1881.

The cor. of Tps. 16 and 17 N., Rs. 27 and 28 E., monumented with a lava stone, 15x10x8 ins., plainly mkd. with 6 grooves on each of four faces and firmly set. The mkd. stone is exposed 4 ins. above the ground and a steel fence post is firmly set alongside. The corner is situated in a fence bearing E. and W.

At the corner point

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N R27E R28E S 36 | S 31 S 1 | S 6 T16N

1967

bury the original corner stone alongside the iron post and reset the steel fence post. Raise a mound of stone 3 ft. base, 2 ft. high, S. of cor.

S. 0° 19' E., along the W. bdy. of sec. 6.

Over gently rolling land, through medium dense undergrowth.

Low bench bears E. and W.; desc. 40 ft. over a rolling S. slope.

Shallow draw, drains ESE.; over nearly level land.

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner now refers to sec. 6 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N R27E R28E |提 S 6

1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

GPO 845-166