

DEPENDENT RESURVEY OF THE SOUTH BDY., T. 17 N., R. 31 E.

CHAINS

N. 89° 53' W., beginning new measurement.

Over nearly level land draining N., through medium dense undergrowth.

1.40 Trail road, bears SE. and NW.

36.18 The closing cor. of secs. 5 and 6, T. 16 N., R. 31 E., hereinafter described.

40.24 The cor. of secs. 5, 6, 31 and 32, monumented with a basalt stone, 14x14x8 ins., firmly set and exposed 6 ins. above the ground, and plainly mkd. with 5 notches on the E. edge and 1 notch on the W. edge. This corner now refers to secs. 31 and 32 only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N	R31E
<u>S 31</u>	<u>S 32</u>
S	6
T16N	R31E

1967

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land gently rolling.

Soil, clay sand to sand.

Undergrowth, sagebrush, thistle, and Indian ricegrass.

N. 89° 57' W., along the S. bdy. of sec. 31.

Over a gently rolling NNE. slope, through medium dense undergrowth; asc. 50 ft.

35.94 The N. ¼ sec. cor. of sec. 6, T. 16 N., R. 31 E., hereinafter described.

40.29 The ¼ sec. cor. of secs. 6 and 31, monumented with a basalt stone, 15x15x8 ins., firmly set and exposed 6 ins. above the ground, and plainly mkd. ¼ on the N. face. This corner now refers to sec. 31 only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N	R31E
<u>¼ S</u>	<u>31</u>
T16N	R31E

1967

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.