DEPENDENT RESURVEY OF THE SOUTH BDY., T. 17 N., R. 31 E. CHAINS N. 89° 59' W., beginning new measurement. Over a gently rolling NNE. slope, through medium dense undergrowth; asc. 80 ft. to the Tp. cor. 6.00 Wash, V-bottom, 4 ft. deep, drains NNE. 35.04 The closing cor. of Tps. 16 N., Rs. 30 and 31 E., hereinafter described. 39.50 The cor. of Tps. 16 and 17 N., Rs. 30 and 31 E., monumented with a steel fence post, firmly set and exposed 4 ft. above the ground with a metal tag attached mkd. Group No. 389, and punched for the proper corner. The original corner monument, a basalt stone, 18x10x8 ins. lies alongside the steel fence post and is mkd. with 6 grooves on each of four faces. This corner now refers to Tps. 17 N., Rs. 30 and 31 E. only. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. **T17N** R30E R31E S 36 S 31 S 1 T16N R30E

1967

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Reset the steel fence post alongside the iron post. The Group No. 389 geographic position data for this corner is: latitude 39° 17' 09.693" N., and longitude 118° 33' 18.909" W. The steel fence post was placed at the true corner point under Group No. 389 and the iron post set under this survey is accurately at this same point.

Land, gently rolling. Soil, clay sand. Undergrowth, sagebrush, thistle, greasewood and Indian ricegrass.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 16 N., R. 31 E., MOUNT DIABLO MERIDAN, NEV.

Reestablishment of a Portion of the Survey Excuted by E. B. Monroe, U. S. Deputy Surveyor, in 1868.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.