SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 16 N., R. 31 E.

CV/AVVC I	
CHAINS	
ŕ	T16N R31E
·	½ S4
	1967
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor
	From this corner, the W. ½ sec. cor. of sec. 3, bears N. 0° 59' W., 3.75 chs. dist.
	From the cor. of secs. 4, 5, 8 and 9.
	N. 0° 03' W., bet. secs. 4 and 5.
	Over gently rolling land draining NE., through medium dense undergrowth; desc. 60 ft. to the ½ sec. cor.
3.70	Wash, 30 lks. wide, 2 ft. deep, drains NE.
22.40	Trail road, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T16N R31E
	S 5 S 4
	1967
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Desc. 40 ft. over gently rolling land draining NE., to the closing cor.
43.60	Trail road, bears SE. and NW.
63.00	Dim track road, bears SE. and NW.
84.40	Intersect the S. bdy. of sec. 33, T. 17 N., R. 31 E.
•	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T17N R31E S 33 S 5 S 4 CC T16N R31E
	1967
1	