

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 16 N., R. 31 E.

CHAINS	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
42.00	Enter sand, bears E. and NW.; desc. 100 ft. over a gentle N. slope.
84.44	Intersect the S. bdy. of sec. 32, T. 17 N., R. 31 E.
	Point for the closing cor. of secs. 5 and 6.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T17N R31E S 32 S 6 S 5 CC T16N R31E 1967 </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the cor. of secs. 31 and 32, T. 17 N., R. 31 E., bears N. $89^{\circ} 53'$ W., 4.06 chs. dist.
	Land, mountainous to gently rolling. Soil, sandy clay and rocky to sand. Undergrowth, sagebrush, shadscale, greasewood and Indian ricegrass.
	<hr/> The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 is on the S. bdy. of sec. 32, T. 17 N., R. 31 E., and at midpoint in departure on the N. bdy. of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T17N R31E <hr/> $\frac{1}{4}$ S 5 T16N R31E 1967 </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the S. $\frac{1}{4}$ sec. cor. of sec. 32, T. 17 N., R. 31 E., bears N. $89^{\circ} 57'$ W., 3.81 chs. dist.
	<hr/> The point for the N. $\frac{1}{4}$ sec. cor. of sec. 6 is on the S. bdy. of sec. 31, T. 17 N., R. 31 E., and at 40.00 chs. in departure from the closing cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.