

DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 33 N., R. 37 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T33N  
R37E R38E  
½  
S 12 | S 7

1967

from which

A well, bears N. 87° 27' E., 17.60 chs. dist.

N. 0° 27' W., beginning new measurement.

Over nearly level land, along fence on W. edge of field.

39.95 Power line, bears E. and W.

40.00 The cor. of secs. 1, 6, 7 and 12, determined at the corner of fence which bears S. and E. This point is locally recognized as the true corner point and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T33N  
R37E R38E  
S 1 | S 6  
S 12 | S 7

1967

Land, nearly level.  
Soil, clay loam.  
Undergrowth, shadscale and greasewood.

N. 0° 15' W., bet. secs. 1 and 6.

Over nearly level land, through medium undergrowth; along a bladed road.

16.20 Trail road, bears E. and W.

39.98 The ¼ sec. cor. of secs. 1 and 6, monumented with an unmarked wooden post, 2x2x20 ins., loosely set in a mound of earth.

At the corner point