

DEPENDENT RESURVEY, E. BDY., T. 32 N., R. 38 E.

CHAINS

At the corner point  
 Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T32N  
 R38E R39E  
 S 1 | S 6  
 S 12 | S 7

1967

bury the original corner stone and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.

Land, gently rolling.  
 Soil, clay loam.  
 Undergrowth, shadscale and budsage.

N. 0° 08' W., bet. secs. 1 and 6.

Over gently rolling land, through medium undergrowth; asc. 80 ft. along a W. slope to the ¼ sec. cor.

- 2.00 Wash, 10 lks. wide, 1 ft. deep, drains WSW.
- 11.00 Trail road, bears SSE. and NNW.
- 17.50 Wash, 10 lks. wide, 1 ft. deep, drains WSW.
- 35.70 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 38.00 Trail road, bears NNE. and SSW.
- 40.00 The ¼ sec. cor. of secs. 1 and 6, monumented with a white granite stone, 6x6x14 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point  
 Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T32N  
 R38E R39E  
 ¼  
 S 1 | S 6

1967

bury the original corner stone and set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.