

RETRACEMENT OF A PORTION OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH R. 43 E.

CHAINS	<p>RETRACEMENT OF A PORTION OF THE SECOND STANDARD PARALLEL NORTH, THROUGH R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Retracement of a Portion of the Survey Executed by C. C. Tracy, U. S. Deputy Surveyor, in 1867 and Resurveyed by H. G. Parker, Cadastral Surveyor, in 1961</p> <hr/> <p>Beginning at the standard cor. of Tps. 11 N., Rs. 43 and 44 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>N. 89° 42' W., along the S. bdy. of sec. 36.</p> <p>Over gently rolling land, draining WNW., through medium dense undergrowth.</p>
2.92	The closing cor. of Tps. 10 N., Rs. 43 and 44 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
40.16	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	<hr/> <p>N. 89° 47' W., beginning new measurement.</p>
2.87	The N. $\frac{1}{4}$ sec. cor. of sec. 1, T. 10 N., R. 43 E., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
20.00	Begin descent; desc. 30 ft. over a gently rolling SW. slope.
40.00	Bladed gravel road, bears N. 4-3/4° E. and S. 4-3/4° W.
40.56	The standard cor. of secs. 35 and 36, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	<hr/> <p>N. 89° 46' W., along the S. bdy. of sec. 35.</p> <p>Over gently rolling land, draining NW., through medium dense undergrowth.</p>
2.82	The closing cor. of secs. 1 and 2, T. 10 N., R. 43 E., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
7.50	Wash, 30 lks. wide, 3 ft. deep, drains NW.
19.50	Wash, 25 lks. wide, 3 ft. deep, drains NW.
30.20	Trail road, bears SE. and NW.