DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 4 S., R. 63 E.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

1967

bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the cor.

Land, rolling.
Soil, clay, loam and gravel.
Vegetation, sagebrush and greasewood.

N. 89° 54° W., bet. secs. 6 and 31.

Over rolling land.

40.21

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a limestone, 8x8x2 ins., mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

1967

bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the cor.

S. 89° 26' W., beginning new measurement.

Over rolling land, through scattered undergrowth.

40.29

The cor. of Tps. 3 and 4 N., Rs. 62 and 63 E., monumented with a lava stone, 14x8x8 ins., mkd. with 6 notches on the N., S., E. and W. edges.