

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,
THROUGH RANGE 65 EAST

CHAINS	
73.90	Trail road, bears N. and S.; fence bears N. $77\frac{1}{2}^{\circ}$ E. and S. $77\frac{1}{2}^{\circ}$ W.
74.50	Cor. of fences, bears south 10 lks. dist.; fences extend N., S., W. and N. $77\frac{1}{2}^{\circ}$ E.
81.40	Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S C T1N R65E <u>S 31 S 32</u> 1970 </div> raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. from this corner, a USC&GS azimuth marker, monumented with a bronze disk, mkd. ELY SPRINGS 1944, set in a drill hole in a boulder, 3x1 ft. above ground, bears N. $57^{\circ} 33'$ W., 3.78 chs. dist. Land, nearly level. Soil, sandy. Vegetation, shadscale and budsage.
	N. $89^{\circ} 40'$ W., along the S. bdy. of sec. 31. Over gradual W. slope, through light brush; desc. 20 ft.
16.055	The $\frac{1}{4}$ sec. cor. of sec. 5, T. 1 S., R. 65 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 1 S., R. 65 E., resurveyed concurrently under this same group. Descend 30 ft. over gradual W. slope.
40.70	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S C T1N R65E <u>$\frac{1}{4}$ S 31</u> 1970 </div> raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.