

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 1 S., R. 65 E.

CHAINS	
40.25	<p>The cor. of secs. 1 and 12, monumented with a limestone, 16x10x6 ins., mkd. with 1 groove on the N. face and 5 grooves on the S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T1S R65E R66E S 1 S 12 </p> <p>1970</p> </div> <p>bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>From this corner, BLM triangulation station U-84-3, monumented with a copperweld, mkd. U-84-3 BLM 1962, firmly set, extending 6 ins. above ground with a mound of stone alongside, bears S. 26° 21' E., 1.32 chs. dist.</p> <p>Land, rolling hills. Soil, rock and clay. Vegetation, budsage and shadscale. Timber, pinon and juniper.</p>
	<p>N. 0° 41' E., along the E. bdy. of sec. 1.</p>
	<p>Over rolling hills, through light timber and brush.</p>
3.20	<p>Wash, 20 lks. wide, 2 ft. deep, drains SW.</p>
19.50	<p>Wash, 20 lks. wide, 2 ft. deep, drains WSW.</p>
26.30	<p>Trail road, bears E. and W.</p>
33.70	<p>Wash, 30 lks. wide, 2 ft. deep, drains SW.</p>
40.09	<p>The ¼ sec. cor. of sec. 1, monumented with a limestone, 14x8x3 ins., mkd. ¼ on the W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to top, with brass cap mkd.</p>