

## DEPENDENT RESURVEY, E. BDY., T. 36 N., R. 39 E.

## CHAINS

- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.
- T36N  
R39E R40E  
 $\frac{1}{4}$   
S 12 | S 7
- 1968
- set a redwood post, 4x4 ins. by 6 ft. long, 3 ft. in the ground, alongside the iron post.
- 52.00 Slough, 80 lks. wide, 4 ft. deep, drains WNW.
- 71.70 Slough, 50 lks. wide, 3 ft. deep, drains NW.
- 80.00 The cor. of secs. 1, 6, 7 and 12, as determined by the corner of fences, bearing E. and N. This fence corner is locally recognized as the corner and is accepted as the best evidence of the position of the original cor.
- At the corner point
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.
- T36N  
R39E R40E  
S 1 | S 6  
S 12 | S 7
- 1968
- Land, nearly level.  
Soil, sandy clay loam.  
Undergrowth, willows and wild meadow grass.
- 
- N.  $0^{\circ} 08' W.$ , bet. secs. 1 and 6.
- Over nearly level land, through medium undergrowth; along fence.
- 19.30 Corner of fences, bearing E., S. and W.
- 34.30 Leave meadow land, enter sand dunes.
- 39.90 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.
- T36N  
R39E R40E  
 $\frac{1}{4}$   
S 1 | S 6
- 1968