

DEPENDENT RESURVEY, T. 36 N., R. 39 E.

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF
T. 36 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Surveys Executed by
A. J. Hatch, U. S. Deputy Surveyor, in 1868 and
H. B. Maxson, U. S. Deputy Surveyor, in 1888.

From the standard cor. of secs. 35 and 36, on the S. bdy.
of the Tp.

N. $0^{\circ} 19'$ E., bet. secs. 35 and 36.

Over nearly level land, through medium undergrowth; desc.
10 ft. over a NE. slope.

13.70 Powerline, bears S. $76\frac{1}{2}^{\circ}$ E. and N. $76\frac{1}{2}^{\circ}$ W.; desc. 20 ft.
over a NE. slope.

22.00 Wash, 20 lks. wide, 2 ft. deep, drains NE.; desc. 30 ft.
over a NE. slope.

40.42 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T36N R39E

$\frac{1}{4}$

S 35 | S 36

1967

set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the
ground, alongside the iron post.

Descend 60 ft. over a NE. slope.

80.84 The cor. of secs. 25, 26, 35 and 36, monumented with a
granite stone, 8x10x16 ins., firmly set in a mound of
stone and plainly mkd. with 1 groove on the E. and S.
faces.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T36N R39E

S 26 | S 25

S 35 | S 36

1967

bury the original cornerstone and set a steel fence post,
 $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron
post and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft.
high, W. of the cor.