

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF T. 36 N., R. 40 E.

CHAINS	
26.80	Wash, 40 lks. wide, 3 ft. deep, drains NW.
33.70	Trail road, bears N. and S.; desc. 30 ft. over a W. slope.
39.70	The standard cor. of secs. 35 and 36, monumented with a granite stone, 10x12x14 ins., firmly set in a mound of stone and plainly mkd. with 1 notch on the E. face and 5 notches on the W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S. C T36N R40E <u>S 35 S 36</u>
	1968
	bury the corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
	From this corner, Cor. No. 1, M.S. 4756, PATMAN No. 5 lode, bears N. 89° 58' W., 0.034 chs. dist., hereinafter described.
	Land, mountainous to gently rolling. Soil, sandy clay and shale rock. Undergrowth, shadscale and greasewood.
DEPENDENT RESURVEY OF THE EAST BOUNDARY OF T. 36 N., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA.	
Reestablishment of the Survey Executed by A. J. Hatch, U.S. Deputy Surveyor, in 1868.	
	From the standard cor. of Tps. 36 N., Rs. 40 and 41 E'.
	N. 2° 11' W., bet. secs. 31 and 36.
	Over mountainous land, through medium undergrowth; desc. 350 ft. over a N. slope.
10.00	Slope changes; desc. 220 ft. along a W. slope.
30.20	Ravine, drains W.; asc. 10 ft. over SW. slope.
34.50	Spur, slopes WNW.; desc. 50 ft. over NW. slope.
39.41	Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.