

DEPENDENT RESURVEY OF THE N. JBDY., T. 37 N., R. 40 E.

CHAINS		
77.90	Ravine, drains SW.; desc. 10 ft. over a SW. slope.	
79.92	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to the cap, 3 ft. base, with brass cap mkd.	
	<div style="text-align: center;"> T38N R40E <u>S 31 S 32</u> S 6 S 5 T37N </div>	
	1969	
	Land, rolling. Soil, sandy clay and shale rock. Undergrowth, shadscale and sagebrush.	
	S. 89° 53' W., bet. secs. 6 and 31.	
	Over gently rolling land, through medium undergrowth; desc. 130 ft. over a W. slope.	
39.96	The ¼ sec. cor. of secs. 6 and 31, monumented with a mound of stone. There is no remaining evidence of the marked stone or wooden stake.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<div style="text-align: center;"> T38N R40E <u>S 31</u> ¼ S 6 T37N </div>	
	1969	
	set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.	
	N. 87° 47' W., beginning new measurement.	
	Over gently rolling land; desc. 20 ft. over a W. slope.	
10.80	Gravel road, bears N. and S.; desc. 60 ft. over a W. slope.	
34.43	The cor. of Tps. 37 and 38 N., Rs. 39 and 40 E., monumented with a redwood post, 4x4 ins., 4 ft. long, firmly set 2 ft. in the ground and plainly scribed. This wooden post is locally recognized as the Tp. cor. and is accepted as the best available evidence of the position of the original corner.	