

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
RANGE 64 EAST

CHAINS

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH RANGE 64 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by Monroe and
Bateman, U. S. Deputy Surveyors, in 1871.

The standard corner of Tps. 16 N., Rs. 64 and 65 E. is
monumented with a juniper tree, 36 ins. diam., mkd. with
6 notches on the E., W. and N. sides.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set
6 ins. in the ground to bedrock and in a mound
of stone, 5 ft. base to cap, for a reference
monument, bears N. 45° E., 20 ft. dist., with
brass cap mkd. T16N R65E S31 RM 20 FT. 1968 and
an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set
8 ins. in the ground to bedrock and in a mound
of stone, 5 ft. base to cap, for a reference
monument, bears N. 45° W., 20 ft. dist., with
brass cap mkd. T16N R64E S36 RM 20 FT. 1968 and
an arrow pointing to the true corner.

N. $89^\circ 18'$ W., along the S. bdy. of sec. 36.

Over mountainous land, through scattering timber and
undergrowth, asc. 210 ft. over an E. slope.

- 7.10 Ridge, bears SSE. and NNW.; desc. 60 ft. over a SW. slope.
12.60 Head of ravine, drains S.; asc. 80 ft. over a SE. slope.
20.80 Ridge, bears N. and S.; desc. 270 ft. over a W. slope.
35.60 Head of ravine, drains S., asc. 20 ft. over an E. slope.
37.30 Spur, slopes S.; desc. 50 ft. over a W. slope.
39.83 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in
the ground to bedrock and in a mound of stone, 4 ft. base
to cap, with brass cap mkd.

SC
T16N R64E
 $\frac{1}{4}$ S 36

1968