

DEPENDENT RESURVEY OF THE WEST BDY., T. 15 N., R. 64 E.

CHAINS

T15N
R63E R64E
 $\frac{1}{2}$
S 12 | S 7

1968

set a steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

47.50 Trail road, bears ENE. and WSW.

81.00 The cor. of secs. 1, 6, 7 and 12, monumented with a squared juniper post, 1x1x14 ins. long, dimly mkd. and firmly set alongside a length of drill steel, 1½ ins. diam., exposed 6 ins. above the ground.

At the corner point.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T15N
R63E R64E
S 1 | S 6
S 12 | S 7

1968

bury the original corner post and the drill steel alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently rolling.
Soil, sandy clay.
Undergrowth, sagebrush.

N. 0° 03' W., bet. secs. 1 and 6.

Along a gently rolling E. slope, through scattered undergrowth.

5.00 Trail road, bears E. and W.

5.20 Wash, 20 lks. wide, 4 ft. deep, drains E.

13.40 Bladed road, bears E. and W.

26.20 U. S. Highway Nos. 6, 50 and 93, bears S. 30½° E., and N. 30½° W.

32.27 Telephone line, bears N. 30½° W. and S. 30½° E.

38.60 Wash, 10 lks. wide, 1 ft. deep, drains E.

39.97 Point for the ½ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.