

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 4 N., R. 48 E.

CHAINS

N. 0° 49' E., beginning new measurement.

Over gently rolling land.

22.50 Trail road, bears SSE. and NNW.

39.35 The cor. of secs. 1, 6, 7 and 12, monumented with a conglomerate stone, 11x6x6 ins., plainly mkd. with 1 notch on the N. edge, 5 notches on the S. edge and firmly set 4 ins. in the ground. The record calls for a wooden stake; however, this monument is harmoniously related to existing corners and is accepted as the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T4N			
R47E	R48E		
S 1	S 6		
S 12	S 7		

1968

bury the corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, nearly level to gently rolling.

Soil, sandy.

Undergrowth, shadscale, budsage and sagebrush.

N. 0° 17' W., bet. secs. 1 and 6.

Over nearly level land, through medium undergrowth.

15.60 Wash, 20 lks. wide, 2 ft. deep, drains E.

32.10 Wash, 10 lks. wide, 3 ft. deep, drains irregularly E.

37.34 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T4N			
R47E	R48E		
S 1	S 6		

1968