

DEPENDENT RESURVEY OF A PORTION OF THE MOUNT DIABLO BASE LINE, THROUGH
RANGE 43 EAST

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE
MOUNT DIABLO BASE LINE, THROUGH RANGE 43 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
A. Ludlum, U. S. Deputy Surveyor, in 1881.

Beginning the resurvey at the standard cor. of secs. 35
and 36, monumented with a lava stone, 13x12x7 ins., plainly
mkd. with 5 notches on the W. edge, 1 notch on the E. edge
and firmly set in a small mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

SC
T1N R43E
S 35 | S 36

1968

bury the original corner stone alongside the iron post and
raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. is situated on the W. edge of Mud Lake.

S. 89° 35' E., along the S. bdy. of sec. 36.

Over dry lake,

40.11 Point for the standard ¼ sec. cor. of sec. 36, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

SC
T1N R43E
¼ S 36

1968

deposit broken glass alongside the iron post and set a
lava stone, 24x12x4 ins., 8 ins. in the ground, N. of cor.

80.22 Point for the standard cor. of T. 1 N., Rs. 43 and 44 E.,
at proportionate distance; there is no remaining evidence
of the original corner.