

DEPENDENT RESURVEY OF A PORTION OF THE NINTH STANDARD  
PARALLEL NORTH, THROUGH RANGE 63 EAST

CHAINS		
	<p>N. 89° 32' W., along the S. bdy. of sec. 31 Over rolling land, through medium undergrowth.</p>	
3.50	Trail road bears NE. and SW.	
39.43	<p>Point for the standard <math>\frac{1}{4}</math> sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T46N R63E <u><math>\frac{1}{4}</math> S 31</u></p> <p style="text-align: center;">1968</p>	
44.00	Crest of low divide bears N. and S.; desc. 160 ft. over a W. slope.	
73.00	Small wash drains N.; asc. slightly to township cor.	
78.86	<p>The standard cor. of Tps. 46 N., Rs. 62 and 63 E., monumented with a basalt stone, 16x10x8 ins., firmly set in a mound of stone and plainly mkd. with 6 notches on the E. and W. edges and SC 46 on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T46N R62E   R63E <u>S 36   S 31</u></p> <p style="text-align: center;">1968</p> <p>bury the marked stone alongside the iron post.</p> <p>Land, gentle rolling. Soil, sandy clay loam and gravel. Undergrowth, sagebrush and native grasses.</p> <hr/>	