DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T, 7 N., R. 27 E.

	. I. / N., R. 2/ E.	
CHAINS		
0.30	Spur, slopes E.; desc. 160 ft. over a N. slope.	
10.20	Ravine, drains WNW.; asc. 150 ft. over a S. slope.	
15.70	Spur, slopes W.; desc. 120 ft. over a NW. slope.	
21.00	Head of wash, drains W.; asc. 150 ft. along a W. slope.	
 34.70	Spur, slopes N. and NW. from S. 10° E.; desc. 40 ft. along top of spur.	
39.08	The ½ sec. cor. of secs. 2 and 3, monumented with a basalt stone, 14x8x3 ins., dimly mkd. ½ on the W. face and firmly set in a small mound of stone.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T7N R27E	
	$\begin{bmatrix} & & & & & & & & & & & & & & & & & & &$	
	1969	
	No suitable trees available within limits.	
•	bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.	
1. * · · · · · · · · · · · · · · · · · ·	The corner is located on a spur, slopes N. 10° E.	
•	N. 0° 26' W., beginning new measurement.	
17 70	Descend 180 ft. over a NW. slope, changing to a W. slope.	
17.70	Spur, slopes N. 10° W.; desc. 260 ft. over a NE. slope.	
25.20	Trail road, bears E. and W.	
33.60	Ravine, drains NW.; asc. 120 ft. over a SW. slope.	
41.40	Spur, slopes W.; desc. 20 ft. over a NW. slope.	
41.81	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the south boundary of T. 8 N., R. 27 E., resurveyed concurrently under this same group.	
	Land, mountainous. Soil, rocky clay. Timber, scattering pinon and cedar. Vegetation, shadscale and budsage.	