## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

CHAINS	T. 7 N., R. 27 E.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
•	T7N R27E
	S 3
	1969
•	bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, E. of cor.
	· · · · · · · · · · · · · · · · · · ·
	N. 1° 10' W., beginning new measurement.
	Descend 70 ft. over a NW. slope, changing to a broken W. slope.
13.20	Head of wash, drains W.; asc. 240 ft. over a S. slope.
20.00	Spur, slopes SW.; desc. 90 ft. along broken W. slope.
41.46	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the south boundary of T. 8 N., R. 27 E., resurveyed concurrently under this same group.
•	Land, mountainous. Soil, rocky clay. Vegetation, budsage and shadscale.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
a	N. 0° 18' W., bet. secs. 32 and 33.
	Over mountainous land, through light brush; desc. 130 ft over a N. slope.
5.10	Rough Creek, 40 lks. wide, course W.; asc. 460 ft. over a broken S. slope.
40.61	The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a granite stone, $15 \times 8 \times 3$ ins., mkd. $\frac{1}{4}$ on the W. face, firmly set in a small mound of stone.
	_
	•