

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
T. 8 N., R. 27 E.

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY T. 8 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA										
	<p>Reestablishment of a Portion of the Survey Executed by R. A. Chase and A. Lash, U. S. Deputy Surveyors, in 1868, and the Resurvey Executed by John G. Booker, U. S. Deputy Surveyor, in 1901.</p>										
	<p>The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a granite stone, 18x8x4 ins., mkd. with 2 notches on the E. edge and 4 notches on the W. edge, firmly set in a small mound of stone.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to top, 4 ft. base, with brass cap mkd.</p>										
	<table> <tr> <td>T8N</td><td>R27E</td></tr> <tr> <td>S 34</td><td>S 35</td></tr> <tr> <td>S 3</td><td>S 2</td></tr> <tr> <td>T7N</td><td></td></tr> <tr> <td>1969</td><td></td></tr> </table>	T8N	R27E	S 34	S 35	S 3	S 2	T7N		1969	
T8N	R27E										
S 34	S 35										
S 3	S 2										
T7N											
1969											
	<p>deposit the original cornerstone alongside the iron post.</p>										
	<p>from this corner</p>										
	<p>The SW. cor. of abandoned house bears N. 73 3/4° E., 7.05 chs. dist.</p>										
	<p>A mine shaft, bears N. 86½° E., 6.05 chs. dist.</p>										
	<p>A mine shaft, bears S. 78½° E., 3.35 chs. dist.</p>										
	<p>S. 89° 58' W., bet. secs. 3 and 34.</p>										
	<p>Over mountainous land, through light brush; desc. 170 ft. over NW. slope, changing to W. slope.</p>										
8.10	<p>Ravine, drains N.; asc. 320 ft. over E. slope.</p>										
18.00	<p>Spur, slopes NNE.; desc. 70 ft. over W. slope.</p>										
23.30	<p>Small wash, drains N.</p>										
26.50	<p>Small wash, drains NNE.; asc. 70 ft. over E. slope.</p>										
32.00	<p>Spur, slopes NNW.; desc. 90 ft. over W. slope.</p>										
40.10	<p>The ¼ sec. cor. of secs. 3 and 34, monumented with a granite stone, 14x8x6 ins., mkd. ¼ on the N. face, firmly set 8 ins. in the ground.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>										