## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES T. 8 N., R. 27 E.

CHAINS	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.
	T8N R27E
	S 5 S 4
	1969
	deposit the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	N. 0° 36' E., beginning new measurement.
	Asc. 40 ft. over SW. slope, changing to W. slope.
20.00	
20.00	Spur, slopes NW.; desc. 150 ft. over N. slope.
44.02	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of the south boundary of T. 9 N., R. 27 E., resurveyed concurrently under this same Group.
	Land, mountainous. Soil, rocky clay. Vegetation, budsage and shadscale.
s.	From the cor. of secs. 8, 9, 16 and 17.
	S. 89° 58' W., bet. secs. 8 and 17.
	Over mountainous land, through light brush; desc. 130 ft. over NW. slope.
6.90	Ravine, drains N.; asc. 80 ft. over NE. slope.
20.20	Spur, slopes N.; desc. 80 ft. over W. slope.
25.30	Wash, drains N.; asc. 60 ft. over NE. slope.
26.50	Trail road, bears N. and S.
30.50	Trail road, bears NE. and SW.
32.00	Wash, drains NNE.
34.40	Wash, drains NE.
40.01	The ½ sec. cor. of secs. 8 and 17, monumented with a basalt stone, 18x14x6 ins., mkd. ½ on the N. face, firmly set in a mound of stone.
	At the corner point