

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 8 N., R. 27 E.

CHAINS	
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 04' W., bet. secs. 5 and 6.
	Over nearly level land, through medium brush; over gradual E. slope.
26.00	Wash, drains E.
28.60	Trail road, bears NNW. and SSE.
34.60	Powerline, bears N. 25½° W. and S. 25½° E.
39.80	Dirt road, bears NW. and SE.
40.07	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<div>T8N R27E ¼ S 6 S 5</div>
	1969
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Over nearly level land.
48.50	Wash, drains ENE.
52.50	Trail road, bears E. and W.
60.50	Fence, bears NNW. and SSE.
72.00	Enter bottom land, edge bears NW. and SE.; desc. 20 ft. over river bank.
76.20	Left bank of East Walker River, bears NNW. and SSE.; thence across river, course NNW.
80.00	Right bank of river, bears NW. and SE.; asc. 30 ft. over S. slope.
84.68	Intersect the S. bdy. of T. 9 N., R. 27 E.
	The closing cor. of secs. 5 and 6, monumented with a trapstone, 18x12x4 ins., mkd. 5 on the SE. edge, CC on the S. face and 6 on the SW. edge, firmly set in a mound of stone.
	At the corner point