## DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 9 N., R. 27 E.

1	CHAINS	
		T9N R27E
		<u>S_32</u>
		S 5
		T8N
		1969
		deposit the original corner stone alongside the iron
		post.
		N. 89° 36' W., beginning new measurement.
		Descend 290 ft. over W. slope.
	9.00	Ravine, drains WSW.; desc. 150 ft. along S. slope.
	16.50	Ravine, drains SW.; asc. 100 ft. over SE. slope.
	29.30	Spur, slopes SW.; desc. 40 ft. over W. slope.
	34.65	The cor. of secs. 31 and 32, monumented with a trapstone, 20x14x11 ins., mkd. with 5 notches on the E. edge and 1 notch on the W. edge, firmly set in a mound of stone.
		At the corner point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T9N R27E
		S 31   S 32
		T8N R27E
		1969
		bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.
		Land, mountainous.
		Soil, rocky clay.
		Vegetation, budsage and shadscale.
		N. 89° 26' W., along the S. bdy. of sec. 31.
	;	Over rolling land, through medium brush; desc. 80 ft.
	·	over W. slope.
	5.59	The closing cor. of secs. 5 and 6, T. 8 N., R. 27 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field note record of T. 8 N., R. 27 E., resurveyed concurrently under this same group.
	6.50	Bottom of descent, slopes S.; trail road, bears N. and S.; asc. 30 ft. over E. slope.
Į	1	1