

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 9 N., R. 27 E.

CHAINS	<p>bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, rocky clay. Vegetation, sagebrush, shadscale and budsage.</p>						
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 9 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p>						
	<p>Reestablishment of a Portion of the Surveys Executed by R. A. Chase, U. S. Deputy Surveyor, in 1869, J. M. Houston, U. S. Deputy Surveyor, in 1889, and John G. Booker, U. S. Deputy Surveyor, in 1902.</p>						
	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a trapstone, 18x18x12 ins., mkd. with 3 notches on the E. edge and 1 notch on the S. edge, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.</p> <table><tr><td>T9N</td><td>R27E</td></tr><tr><td>S 28</td><td>S 27</td></tr><tr><td>S 33</td><td>S 34</td></tr></table> <p>1969</p> <p>deposit the original corner stone alongside the iron post.</p> <p>N. 0° 08' W., bet. secs. 27 and 28.</p> <p>Over mountainous land, through light brush; asc. 20 ft. over SW. slope.</p> <p>3.30 Spur, slopes NW.; desc. 290 ft. over N. slope.</p> <p>24.10 Wash, 200 lks. wide, 2 ft. deep, drains NW.; asc. 160 ft. over SW. slope.</p> <p>33.10 Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>39.97 The ¼ sec. cor. of secs. 27 and 28, monumented with a granite stone, 18x8x6 ins., mkd. ¼ on the W. face, firmly set in a mound of stone.</p>	T9N	R27E	S 28	S 27	S 33	S 34
T9N	R27E						
S 28	S 27						
S 33	S 34						