DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 10 N., R. 27 E.

CHAIN

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY T. 10 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by R. A. Chase and A. Lash, U. S. Deputy Surveyors, in 1868, and the Retracement and Partial Resurvey Executed by John G. Booker, U. S. Deputy Surveyor, in 1902.

Beginning the resurvey at the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a sandstone, $20 \times 10 \times 8$ ins., plainly mkd. with 3 notches on the E. edge, 3 notches on the W. edge and firmly set in a small mound of earth.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

1968

bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

N. 89° 21' W., bet. secs. 4 and 33.

Over gently rolling land, through medium undergrowth; desc. 70 ft. over a gradual W. slope to the ½ sec. cor.

- 9.50 Trail road, bears SSE, and NNW.
- 11.80 Trail road, bears SE. and NW.
- 19.40 | Trail road, bears N. and S.
- 19.60 Fence, bears N. and S.
- 35.00 Bottom of descent, bears N. and S.; thence over nearly level bottom land.
- 39.94 Point for the ½ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.