

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 10 N., R. 27 E.

CHAINS

- 14.50 Ravine, drains SE.; asc. 210 ft. over an E. slope.
- 35.33 The closing cor. of secs. 5 and 6, T. 9 N., R. 27 E., monumented with a sandstone, 18x9x9 ins., plainly mkd. CC on the S. face, 6 on the SW. face, 5 grooves on the E. face, 5 on the SE. face and firmly set in the ground with a mound of stone S. of cor.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T10N R27E

S 32

S 6 | S 5

T9N

CC

1968
- bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
- Asc. over a gradual E. slope.
- 38.00 Top of ridge, bears NW. and E.; desc. 30 ft. over a SW. slope.
- 40.20 The cor. of secs. 31 and 32, monumented with a sandstone, 20x8x6 ins., plainly mkd. with 5 notches on the E. edge, 1 notch on the W. edge and firmly set in a mound of stone. This cor. now becomes an angle point on the S. bdy. of sec. 32.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to bedrock and in a mound of stone to top, 6 ft. base, with brass cap mkd.
- AP

T10N R27E

S 32

T9N

1968
- deposit the original corner stone alongside the iron post.
-
- N. $89^{\circ} 36'$ W., beginning new measurement.