

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 27 E.

CHAINS	
36.00	Spur, slopes W.; desc. 30 ft. over a W. slope.
39.70	Ravine, drains SW.; asc. 20 ft. over a SE. slope.
41.92	Intersect the Second Standard Parallel North.
	The closing cor. of secs. 4 and 5, monumented with a trapstone, 18x9x8 ins., plainly mkd. with 4 grooves on the E. face, 6 grooves and CC on the S. face, 2 grooves on the W. face and firmly set in the ground with a mound of stone S. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div>T11N R27E S 32 S 5 S 4 T10N CC</div>
	1968
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner
	The standard ¼ sec. cor. of sec. 32, T. 11 N., R. 27 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 17' W., 14.62 chs. dist.
	An angle point (original standard cor. of secs. 32 and 33, T. 11 N., R. 27 E., monumented with a trapstone, 14x9x6 ins., plainly mkd. AP on the N. face and firmly set in a mound of stone, bears S. 89° 17' E., 21.72 chs. dist.
	At the angle point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div>AP T11N R27E S 32</div>
	1968