

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 N., R. 27 E.

CHAINS

40.96

Point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T10N R27E

$$\begin{array}{c} \frac{1}{2} \\ S \ 6 \ | \ S \ 5 \end{array}$$

1968

deposit broken glass alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

Asc. gradually over a gentle W. slope.

55.50

Power line, bears S. 34° E. and N. 34° W.

80.00

Intersect the Second Standard Parallel North.

The closing cor. of secs. 5 and 6, monumented with a quartz stone, 15x9x8 ins., plainly mkd. with 5 notches on the E. edge, 6 notches and CC on the S. edge, 1 notch on the W. edge and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T11N R27E

$$\begin{array}{c} S \ 31 \\ \hline S \ 6 \ | \ S \ 5 \end{array}$$

T10N

CC

1968

bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

From this corner

The standard $\frac{1}{2}$ sec. cor. of sec. 31, T. 11 N., R. 27 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears S. $89^\circ 40'$ W., 14.44 chs. dist.

An angle point (original standard cor. of secs. 31 and 32, T. 11 N., R. 27 E.), monumented with a trapstone, 12x7x6 ins., plainly mkd. AP on the N. face and firmly set in a mound of stone, bears N. $89^\circ 40'$ E., 21.30 chs. dist.