DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 N., R. 27 E.

T. 10 N., R. 27 E.	
CHAINS	
	AP
5.9	T11N R27E S 31
	1968
	1900
	bury the original corner stone alongside the
	iron post and raise a mound of stone, 2 ft. base, 2 ft. high, N. of angle point
	, 2 2 3 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
	SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
	T. 10 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the cor. of secs. 31 and 32, on the S. bdy. of the
	Tp.
	N. 0° 01' E., bet. secs. 31 and 32.
	N. O OI I., Bet. Bees. 31 and 32.
	Over mountainous land, through medium undergrowth; asc.
	60 ft. over a S. slope.
3,50	Spur, slopes SE.; desc. 50 ft. over a NE. slope.
8.00	Bottom of descent; asc. 20 ft. over a SE. slope.
15.30	Top of ascent on E. slope; desc. gradually over an E. slope.
18.00	Spur, slopes NE.; desc. 80 ft. over a W. slope.
22.50	Ravine, drains NNE. into next ravine; desc. 20 ft. over a gradual NNE. slope.
28.60	Ravine, drains NE.; enter over rolling land, sloping E.
40,.38	Point for the ½ sec. cor. of secs. 31 and 32, at 40.00 chs. in latitude from the cor. of secs. 29, 30, 31 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
c	TION POTE
	T10N R27E s 31 s 32
	S 31 S 32
	1968
	deposit broken glass and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
	10116, 2 10. In the ground, arongoide the front poor.
-	