

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
T. 42 N., R. 20 E.

CHAINS									
81.02	<p>Continue over nearly level land, through medium dense sagebrush, rabbitbrush and greasewood.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T43N</td><td>R20E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>T42N</td><td>R20E</td></tr> </table> <p>1968</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T43N	R20E	S 31	S 32	S 6	S 5	T42N	R20E
T43N	R20E								
S 31	S 32								
S 6	S 5								
T42N	R20E								
40.51	<p>N. 88° 03' W., bet. secs. 6 and 31.</p> <p>Over nearly level land, through medium dense sagebrush and rabbitbrush.</p> <p>The ¼ sec. cor. of secs. 6 and 31, monumented with a sawed pine board, 1x2x40 ins., plainly mkd. N ¼ VI on S. face and S ¼ XXXI on the N. face, lying on a small mound of earth. The record call is for a stone monument. This point is accepted as the best remaining evidence of the position of original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T43N</td><td>R20E</td></tr> <tr><td>¼</td><td>S 31</td></tr> <tr><td>S 6</td><td></td></tr> <tr><td>T42N</td><td>R20E</td></tr> </table> <p>1968</p> </div> <p>deposit the marked board alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	T43N	R20E	¼	S 31	S 6		T42N	R20E
T43N	R20E								
¼	S 31								
S 6									
T42N	R20E								
37.10	<p>N. 88° 04' W., beginning new measurement.</p> <p>Over nearly level land, through medium dense sagebrush and rabbitbrush.</p> <p>Fence, bears S. 20° E. and N. 20° W.</p>								