

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 42 N., R. 21 E.

CHAINS	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Desc. 50 ft. along a rolling E. slope.
80.00	Ravine, drains NNW.; asc. 10 ft. over a SW. slope.
83.22	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>T42N R21E R22E S 1 S 6 S 12 S 7 1968</div>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 12' W., bet. secs. 1 and 6. Over rolling land, through medium dense to scattered sagebrush. Asc. 80 ft. over a SW. slope.
11.30	Fence, bears E. and W. at low spur sloping W.; desc. 20 ft. over a N. slope.
18.20	Dim track road, bears E. and W. along shallow draw draining W.; asc. 30 ft. over a SW. slope to the ¼ cor.
33.00	Trail road, bears NE. and SW.
41.61	The ¼ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 8x5x4 ins., plainly mkd. ¼ on the W. face and firmly set in a collar of imbedded stone. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>T42N R21E R22E ¼ S 1 S 6 1968</div>
	bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 35' W., beginning new measurement.