DEPENDENT RESURVEY OF THE SOUTH BOUNDARY T. 14 N. R. 56 E.

	T. 14 N., R. 56 E.
CHAINS	
	N. 89° 45' W., bet. secs. 5 and 32.
	Over gently rolling land, through scattered undergrowth; desc. 120 ft. over W. slope.
40.06	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T14N R56E S 32 S 5 T13N
	1968
	raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	Desc. 90 ft. over gentle W. slope.
80.12	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T14N R56E S 31 S 32 S 6 S 5 T13N
	1968 - 19
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, gently rolling.
	Soil, sandy clay and gravel.
	Undergrowth, sagebrush and greasewood.
	N. 89° 45' W., bet. secs. 6 and 31.
	Over gently rolling land, through scattered undergrowth; desc. 40 ft. over a gentle W. slope to 2 sec. cor.
10.80	Bladed road, bears NNE. and SSW.
40.06	Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.