

## DEPENDENT RESURVEY, THIRD STANDARD PARALLEL NORTH, R. 56 E.

CHAINS	
	<p>N. 89° 56' W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through scattered timber and undergrowth; asc. 70 ft. over an E. slope to top of spur.</p>
5.52	The closing cor. of secs. 5 and 6, T. 15 N., R. 56 E., hereinafter described.
7.40	Low spur, bears N. and S.; desc. 110 ft. over W. slope.
40.61	<p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 31, monumented with a basalt stone, 14x8x6 ins., dimly mkd. <math>\frac{1}{4}</math> on N. face and firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R56E <u><math>\frac{1}{4}</math> S 31</u></p> <p style="text-align: center;">1969</p> <p>bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89° 54' W., beginning new measurement.</p> <p>Over rolling land.</p>
2.60	Bladed road, bears N. and S.
4.91	The N. $\frac{1}{4}$ sec. cor. of sec. 6, T. 15 N., R. 56 E., hereinafter described.
5.00	Wash, 10 lks. wide, 2 ft. deep, drains SSW.
5.90	Wash, 10 lks. wide, 2 ft. deep, drains S.
26.40	Trail road, bears NE. and SW.
40.65	<p>The standard cor. of Tps. 16 N., Rs. 55 and 56 E., monumented with a squared wooden post, 36 ins. long, 2 ins. square, plainly scribed and firmly set alongside a steel fence post. This corner will now function as the standard cor. of T. 16 N., R. 56 E. only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>