

SURVEY OF THE SUBDIVISIONAL LINES OF T. 15 N., R. 56 E.

CHAINS

N. 0° 01' W., bet. secs. 2 and 3.

Over rolling mountainous land, through medium timber and undergrowth; desc. 50 ft. along NW. slope.

- 6.10 Wash, 10 lks. wide, 4 ft. deep, drains W.; asc. 30 ft. over SW. slope.
- 13.30 Spur, slopes SW.; desc. 170 ft. over NW. slope.
- 26.80 Wash, 18 lks. wide, 2 ft. deep, drains NW.; asc. 20 ft. over SW. slope.
- 33.00 Spur, slopes WNW.; desc. 50 ft. over N. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T15N R56E

S $3\frac{1}{2}$ | S 2

1969

Desc. 80 ft. over rolling N. slope.

- 44.40 Wash, 10 lks. wide, 3 ft. deep, drains W.; asc. 140 ft. over SW. slope.
- 69.60 Spur, slopes W.; desc. 140 ft. over NW. slope.
- 78.20 Wash, 10 lks. wide, 3 ft. deep, drains W.
- 83.17 Intersect the Third Standard Parallel North.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16N R56E

S 34

S 3 | S 2

T15N | R56E

CC

1969

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner the standard cor. of secs. 34 and 35, T. 16 N., R. 56 E., heretofore described, bears S. 89° 51' E., 7.85 chs. dist.