INDEPENDENT	RESU	RVEY	of	THE	SOUTH	BOUNDARY,
	т	20 1	AT .	D A	60 E	

Land, gently rolling. Soil, sandy clay and gravel. Undergrowth, sagebrush and greasewood.  EAST, bet. secs. 1 and 36.  Over gently rolling land, through scattered undergrowth; desc. 50 ft. over gentle E. slope to the ½ sec. cor.  7.80  Wash, 15 lks. wide, 3 ft. deep, drains NE.  Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E ½ S 36 ½ S 1  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  68.40  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E S 36   S 31 S 1   S 6 T28N  1969	1	1. 25 N. 9 N. 05 L.				
Soil, sandy clay and gravel. Undergrowth, sagebrush and greasewood.  EAST, bet. secs. 1 and 36.  Over gently rolling land, through scattered undergrowth; desc. 50 ft. over gentle E. slope to the ½ sec. cor.  7.80  Wash, 15 lks. wide, 3 ft. deep, drains NE.  40.00  Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E  ½ S 36  S 1  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  68.40  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Land, gently rolling. Soil, sandy clay and gravel.	CHAINS	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor				
EAST, bet. secs. 1 and 36.  Over gently rolling land, through scattered undergrowth; desc. 50 ft. over gentle E. slope to the ½ sec. cor.  7.80  Wash, 15 lks. wide, 3 ft. deep, drains NE.  40.00  Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E  2 S 36  3 1  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  68.40  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E.  This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36 S 31  S 1 S 1 S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor  Land, gently rolling. Soil, sandy clay and gravel.						
Over gently rolling land, through scattered undergrowth; desc. 50 ft. over gentle E. slope to the ½ sec. cor.  7.80 Wash, 15 lks. wide, 3 ft. deep, drains NE.  40.00 Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E  ½ S 36  8 1  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  Trail road, bears NNE. and SSW.  80.00 Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31  S 1   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		Undergrowth, sagebrush and greasewood.				
desc. 50 ft. over gentle E. slope to the ½ sec. cor.  7.80 Wash, 15 lks. wide, 3 ft. deep, drains NE.  40.00 Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E  ½ S 36  ½ S 36  ½ S 1  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  Trail road, bears NNE. and SSW.  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36 S 31 S 1 S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		EAST, bet. secs. 1 and 36.				
Point for the ½ sec. cor. of secs. 1 and 36.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E ½ S 36 ½ S 1 T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  Trail road, bears NNE. and SSW.  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N R69E R70E S 36   S 31 S 1   S 6 T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.						
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.  T29N R69E  \[ \frac{1}{8} \frac{3}{6} \]  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cord of the cor	7.80	Wash, 15 lks. wide, 3 ft. deep, drains NE.				
in the ground, with brass cap mkd.  T29N R69E  \( \frac{1}{8} \) \frac{36}{5} \)  1 T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  88.40  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2\frac{1}{2} ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  \( \frac{3}{36} \) \frac{31}{5}  \frac{1}{3}  \frac{6}{6} \)  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor  Land, gently rolling. Soil, sandy clay and gravel.	40.00	Point for the ½ sec. cor. of secs. 1 and 36.				
Taile a mound of stone, 3 ft. base, 2 ft. high, N. of cores.  80.00  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36 S 31  S 1 S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of core Land, gently rolling. Soil, sandy clay and gravel.						
T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  68.40  Trail road, bears NNE. and SSW.  80.00  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31   S 6   T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.						
raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor  68.40 Trail road, bears NNE. and SSW.  80.00 Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31  S 1   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		_				
Trail road, bears NNE. and SSW.  Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31  S 1   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		1969				
Point for the cor. of Tps. 28 and 29 N., Rs. 69 and 70 E. This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor				
This position is calculated to be due North of a point on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and 69 E.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  T29N  R69E R70E  S 36   S 31  S 1   S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.	68.40	Trail road, bears NNE. and SSW.				
in the ground, with brass cap mkd.  T29N  R69E R70E  S 36 S 31  S 1 S 6  T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor  Land, gently rolling.  Soil, sandy clay and gravel.	80.00	on the Fifth Standard Parallel North which is 480.00 chains East of the standard cor. of T. 26 N., Rs. 68 and				
R69E R70E S 36 S 31 S 1 S 6 T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.						
S 36 S 31 S 1 S 6 T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.						
T28N  1969  raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		S 36 S 31				
raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor Land, gently rolling. Soil, sandy clay and gravel.		;				
Land, gently rolling. Soil, sandy clay and gravel.		1969				
Soil, sandy clay and gravel.		raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor				
		Soil, sandy clay and gravel.				