

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 40 N., R. 46 E.

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R45E R46E S 12 S 7 1970</p> <p>raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor. Descend 70 ft. along E. slope.</p> <p>54.10 Head of ravine, drains E.; asc. 120 ft. along E. slope.</p> <p>64.50 Top of ascent; desc. 160 ft.</p> <p>80.58 The cor. of secs. 1, 6, 7 and 12, monumented with a mound of stone partially imbedded in the ground, no marked stone found; this position is harmoniously related to other existing corners found in the survey and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R45E R46E S 1 S 6 S 12 S 7 1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
	<p>N. 9° 26' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through medium sagebrush; desc. 340 ft. along E. slope to the ¼ sec. cor.</p> <p>8.60 Wash, 15 lks. wide, 3 ft. deep, drains NE.</p> <p>45.32 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R45E R46E S 1 S 6 1970</p>	