

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 46 E.

CHAINS		
	<p style="text-align: center;">T40N R46E $\frac{3}{4}$ S 35 S 36</p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.</p> <p>Ascend 10 ft. over E. slope.</p>	
46.80	Draw, drains SE.; asc. 390 ft. along E. slope.	
86.50	Ridge, bears NNE. and SSW.; desc. 50 ft. along W. slope.	
91.14	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a mound of stone, with a 2x2 in. wooden hub in center of the mound; this position is harmoniously related to other existing corners found in the township, and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R46E S 26 S 25 S 35 S 36</p> <p style="text-align: center;">1970</p> <p>reset the wooden hub alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the W. bdy. of T. 40 N., R. 47 E.</p> <p>N. 78° 55' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through medium sagebrush; asc. 60 ft.</p>	
38.26	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R46E $\frac{1}{4}$ S 25 S 36</p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>	