

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 46 E.

CHAINS	
	Continue along rolling N. slope; desc. gradually.
43.00	Wash, 15 lks. wide, 3 ft. deep, drains NNE.; asc. 130 ft.
48.00	Spur, slopes NNE.; desc. 80 ft.
74.80	Wash, 15 lks. wide, 3 ft. deep, drains NNE.; asc. 60 ft.
81.44	The cor. of secs. 2, 3, 10 and 11.
	N. 10° 51' E., bet. secs. 2 and 3.
	Over rolling land, through medium sagebrush; desc. gradually.
14.20	Trail road, bears NE. and SW.
46.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T40N R46E <math>\frac{1}{4}</math> S 3   S 2</p>
	1970
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Over gently rolling land, descending gradually.
181.06	Intersect the Eighth Standard Parallel North.
	The closing cor. of secs. 2 and 3, monumented with a wooden post, 2x2x36 ins., illegible scribe marks visible, and loosely set in a mound of earth.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T41N R47E <u>S 31.</u> S 3   S 2 C C T40N R46E</p>
	1970
	reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.