DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 40 N., R. 46 E.

	T. 40 N., R. 46 E.
CHAINS 45.78	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T40N R46E
	S 6 S 5
	1970
•	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Descend gradually over gentle N. slope to the closing cor.
117.50	Fence, bears NE. and SW.
118.30	Wash, 15 lks. wide, 2 ft. deep, drains NW.
181.10	Intersect the Eighth Standard Parallel North.
•	Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T41N S 34 S 6 S 5 C C T40N R46E
	1970
,	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this cor., the standard ½ sec. cor. of sec. 34, T. 41 N., R. 46 E., bears S. 89° 48' E., 20.32 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the Eighth Standard Parallel North, through a portion of R. 46 E.
	Point for the N. ½ sec. cor. of secs. 5, on the Eighth Standard Parallel North, and at midpoint on the N. bdy. of sec. 5.
,	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.